

# Package: splineCox (via r-universe)

December 19, 2024

**Type** Package

**Title** A Two-Stage Estimation Approach to Cox Regression Using M-Spline Function

**Version** 0.0.1

**Maintainer** Ren Teranishi <ren.teranishi1227@gmail.com>

**Description** Implements a two-stage estimation approach for Cox regression using five-parameter M-spline functions to model the baseline hazard. It allows for flexible hazard shapes and model selection based on log-likelihood criteria.

**License** GPL (>= 3)

**Encoding** UTF-8

**RoxygenNote** 7.3.2

**Roxygen** list(markdown = TRUE)

**Imports** joint.Cox

**Suggests** knitr, rmarkdown, spelling

**VignetteBuilder** knitr

**Language** en-US

**Repository** <https://ren1227.r-universe.dev>

**RemoteUrl** <https://github.com/ren1227/splinecox>

**RemoteRef** HEAD

**RemoteSha** 7adfdadd236d720f87463d5364e06dbc5d8fc24c

## Contents

splineCox.reg1	2
splineCox.reg2	3

<b>Index</b>	<b>5</b>
--------------	----------

splineCox.reg1

*Fitting the five-parameter spline Cox model giving a specified shape***Description**

splineCox.reg1 estimates the parameters of a five-parameter spline Cox model based on a specified shape for the baseline hazard function. The function calculates the estimates for the model parameters (beta) and the baseline hazard scale parameter (gamma), using non-linear optimization.

**Usage**

```
splineCox.reg1(
  t.event,
  event,
  Z,
  xi1 = min(t.event),
  xi3 = max(t.event),
  model = "constant",
  p0 = rep(0, 1 + ncol(as.matrix(Z)))
)
```

**Arguments**

t.event	a vector for time-to-event
event	a vector for event indicator (=1 event; =0 censoring)
Z	a matrix for covariates; nrow(Z)=sample size, ncol(Z)=the number of covariates
xi1	lower bound for the hazard function; the default is min(t.event)
xi3	upper bound for the hazard function; the default is max(t.event)
model	A character string specifying the shape of the baseline hazard function. Available options include: "increase", "constant", "decrease", "unimodal1", "unimodal2", "unimodal3", "bathtub1", "bathtub2", "bathtub3". Default is "constant"
p0	Initial values to maximize the likelihood (1 + p parameters; baseline hazard scale parameter and p regression coefficients)

**Value**

A list containing the following components:

model	A character string indicating the shape of the baseline hazard function used.
parameter	A numeric vector of the parameters defining the baseline hazard shape.
beta	A named vector with the estimates, standard errors, and 95% confidence intervals for the regression coefficients
gamma	A named vector with the estimate, standard error, and 95% confidence interval for the baseline hazard parameter
loglik	A named vector containing the log-likelihood (LogLikelihood), Akaike Information Criterion (AIC), and Bayesian Information Criterion (BIC)

**Examples**

```
# Example data
library(joint.Cox)
data(data0varian)
t.event = data0varian$t.event
event = data0varian$event
Z = data0varian$CXCL12

reg1 <- splineCox.reg1(t.event, event, Z, model = "constant")
print(reg1)
```

---

splineCox.reg2	<i>Fitting the five-parameter spline Cox model with a specified shape, selecting the best fit</i>
----------------	---

---

**Description**

splineCox.reg2 estimates the parameters of a five-parameter spline Cox model for multiple specified shapes and selects the best fitting model based on the minimization of the log-likelihood function. The function calculates the estimates for the model parameters (beta) and the baseline hazard scale parameter (gamma), using non-linear optimization.

**Usage**

```
splineCox.reg2(
  t.event,
  event,
  Z,
  xi1 = min(t.event),
  xi3 = max(t.event),
  model = names(shape.list),
  p0 = rep(0, 1 + ncol(as.matrix(Z)))
)
```

**Arguments**

t.event	a vector for time-to-event
event	a vector for event indicator (=1 event; =0 censoring)
Z	a matrix for covariates; nrow(Z)=sample size, ncol(Z)=the number of covariates
xi1	lower bound for the hazard function; the default is min(t.event)
xi3	upper bound for the hazard function; the default is max(t.event)
model	A character vector specifying which model shapes to consider for the baseline hazard. Available options are: "increase", "constant", "decrease", "unimodal1", "unimodal2", "unimodal3", "bathtub1", "bathtub2", "bathtub3". Default is names(shape.list) which includes all available models.
p0	Initial values to maximize the likelihood (1 + p parameters; baseline hazard scale parameter and p regression coefficients)

**Value**

A list containing the following components:

model	A character string indicating the shape of the baseline hazard function used.
parameter	A numeric vector of the parameters defining the baseline hazard shape.
beta	A named vector with the estimates, standard errors, and 95% confidence intervals for the regression coefficients
gamma	A named vector with the estimate, standard error, and 95% confidence interval for the baseline hazard parameter
loglik	A named vector containing the log-likelihood (LogLikelihood), Akaike Information Criterion (AIC), and Bayesian Information Criterion (BIC) for the best-fitting model
other_models	A data frame containing the log-likelihood (LogLikelihood) for all other evaluated models, with model names as row names.

**Examples**

```
# Example data
library(joint.Cox)
data(dataOvarian)
t.event = dataOvarian$t.event
event = dataOvarian$event
Z = dataOvarian$CXCL12

M = c("constant", "increase", "decrease")
reg2 <- splineCox.reg2(t.event, event, Z, model = M)
print(reg2)
```

# Index

splineCox.reg1, 2

splineCox.reg2, 3